

DECLARATION OF PERFORMANCE

No 1.4404

| Unique identification code of the product- Intended use/es: Manufacturer: System/s of AVCP: | | for co | onstruction purpo | f corrosion resisting steels | |
|---|---|--|---|--|--|
| | | | kumnu Nirosta Gr | | |
| System/s of AVCP: | | Outokumpu Nirosta GmbH Oberschlesienstr. 16, 47807 Krefeld, Germany | | | |
| System/s of AVCP: | | 2+ | | | |
| Harmonised standard: Notified body/ies: | | EN 10088-4:2009 MPA NRW No.0432 No. 0432-CPR-00052-1 | | | |
| Declared performance/s: | | | | | |
| Essential characteristics | Performance | | mance | Harmonised technical specification | |
| Tolerances on dimensions and shape | Tolerances in accordance with EN ISO 9444-2 and EN ISO 9445-2 | | | EN 10088-4:2009, Clause 6.9 | |
| 0,2%-proof strength (yield strength) Rp0,2 Tensile strength Rm Elongation A Impact strength KV | Cold rolled 240 Mpa 530-680 MF 40 % | Pa | Hot rolled 220 Mpa 530-680 Mpa 40 % 60 J (transverse) | EN 10088-4:2009, Clause 6.5.1 | |
| Weldability | (covered by chemical composition) | | | EN 10088-4:2009, Clause 6.3 | |
| Durability | (covered by chemical composition) | | nical composition) | EN 10088-4:2009, Clause 6.3 and 6.4 | |
| Fracture toughness/ prittle strength | (covered by | / impa | ct strength) | EN 10088-4:2009, Clause 6.5.1 | |
| Cold formability | (covered by elongation) | | gation) | EN 10088-4:2009, Clause 6.8 | |
| Appropriate Technical Documentation and/or Specific Technical Documentation: | | | No. 0432-CPR-00052-1 EN 10088-4:2009, annex ZA | | |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 574/2014, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Krefeld, 24.09.2019

Nico Malinowsky - Inspector (EU-O-KB-QM-A)