

SAFETY DATA SHEET

Issuing Date 26-Nov-2012 Revision Date 20-Nov-2017 Revision Number 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier

Product Name Chromium-Nickel-Manganese-Copper Alloyed Stainless Steel grades

Other means of identification

Synonyms 204Cu. This includes all listed grades with letter prefixes and suffixes as well as PRODEC®

suffix.

Recommended use of the chemical and restrictions on use

Recommended Use Solid stainless steel products, various forms, and uses

Uses advised against No information available

Supplier's details

Supplier Address

Outokumpu Stainless Bar, LLC 3043 Crenshaw Parkway Richburg, SC 29729

TEL: 1-888-458-4600; 1-803-789-5383

Outokumpu Stainless USA, LLC One Steel Drive Calvert, AL 36513 TEL: 1-251-829-3600

Outokumpu Mexinox S.A de C.V AV. Industrias No. 4100 Zona Industrial 1a. Sección 78395, San Luis Potosí, México TEL: +52+444+826-5100

Emergency telephone number

Emergency Telephone

251-829-3600

Number

2. HAZARDS IDENTIFICATION

Classification

This chemical is not considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200).

Solid metallic products are generally classified as "articles" and do not constitute hazardous materials in solid form. However, downstream use of the article could result in some hazardous elements contained in these products to be emitted under certain processing conditions such as but not limited to: burning, melting, cutting, sawing, brazing, grinding, machining, milling, and welding. The classification given below pertains to these alloys when used during these processes.

Acute Oral Toxicity	Category 4
Respiratory Sensitization	Category 1
Skin Sensitization	Category 1
Carcinogenicity	Category 1B

Revision Date 20-Nov-2017

Specific Target Organ Toxicity (Repeated Exposure)

Category 1

GHS Label elements, including precautionary statements

Emergency Overview

Signal Word

Danger

Hazard Statements

- Harmful if swallowed
- May cause allergy or asthma symptoms or breathing difficulties if inhaled
- May cause an allergic skin reaction
- May cause cancer
- Causes damage to organs through prolonged or repeated exposure





Appearance Varying from dull very light grey, to shiny metallic light grey to bright mirror-finish

Physical State Solid.

Odor Odorless

Precautionary Statements

Prevention

- · Wash face, hands and any exposed skin thoroughly after handling
- Do not eat, drink or smoke when using this product
- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required
- In case of inadequate ventilation wear respiratory protection
- · Contaminated work clothing should not be allowed out of the workplace
- Do not breathe dust/fume/gas/mist/vapors/spray

General Advice

• IF exposed or concerned: Get medical attention/advice

Skin

- IF ON SKIN: Wash with plenty of soap and water
- If skin irritation or rash occurs: Get medical advice/attention
- · Wash contaminated clothing before reuse

Inhalation

- IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing
- If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician

Ingestion

- IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
- · Rinse mouth

Storage

• Store in accordance with local/regional/national regulations.

Disposal

• Dispose of in accordance with local/regional/national regulations.

grades

Hazard Not Otherwise Classified (HNOC)

Not applicable

Other information

No information available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms

204Cu. This includes all listed grades with letter prefixes and suffixes as well as PRODEC® suffix.

Chemical Name	CAS-No	Weight %	Trade secret
Iron	7439-89-6	Balance	*
Chromium	7440-47-3	15.5-17.5	*
Manganese	7439-96-5	6.5-9	*
Copper	7440-50-8	2-4	*
Nickel	7440-02-0	1.5-3.5	*
Silicon	7440-21-3	0-1	*
Cobalt	7440-48-4	0-0.6	*
Titanium	7440-32-6	0-0.5	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of necessary first-aid measures

General Advice In its solid form stainless steel does not present an inhalation, absorption, or ingestion

hazard. Grinding, polishing, abrasive blasting, hot rolling, hot forging, thermal cutting, or welding may produce stainless steel dust or fumes containing complex or mixed oxides (spinels) of its components. Metal dust particles may cause eye, skin and/or respiratory

system irritation. The below information is for these instances.

Eye Contact Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

Skin Contact Wash off immediately with soap and plenty of water. In the case of skin irritation or allergic

reactions see a physician.

Inhalation Move to fresh air. If breathing is difficult, give oxygen. Consult a physician.

Ingestion Not an expected route of exposure. If swallowed: Get medical attention.

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects Coughing and/ or wheezing. Difficulty in breathing. Irritation. May cause allergic skin

reaction.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician May cause sensitization by inhalation and skin contact. Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media None

WPS-OUT-004 - Chromium-Nickel-Manganese-Copper Alloyed Stainless Steel Revision Date 20-Nov-2017 grades

Specific Hazards Arising from the Chemical

Avoid dust formation. Dust can form an explosive mixture in air. May cause sensitization by inhalation and skin contact.

Explosion Data

Sensitivity to Mechanical Impact None
Sensitivity to Static Discharge None

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Avoid dust formation. Avoid inhalation of dust. Ensure adequate ventilation. In case of

insufficient ventilation wear suitable respiratory equipment. Use personal protective

equipment. Avoid contact with skin, eyes and clothing.

Environmental Precautions

Environmental Precautions Not applicable to steel in solid state. Follow applicable federal, state and local regulations

Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so. Cover dust spill with plastic sheet or tarp

to minimize spreading.

Methods for Cleaning UpTake up mechanically and collect in suitable container for disposal. Avoid dust formation.

Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Handle in accordance with good industrial hygiene and safety practice. Avoid dust

formation. Avoid breathing dust. Avoid contact with skin, eyes and clothing. Wear personal

protective equipment. Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage Store in accordance with local regulations.

Incompatible Products May react in contact with strong acids to release gaseous acid decomposition products, e.g.

hydrogen, oxides of nitrogen. Use of strong oxidizers (high pH) on stainless steel may cause Cr(VI) compounds to form at ambient temperatures. Decomposition: Fumes generated during welding, brazing, or thermal cutting may contain: chromium compounds, including hexavalent chromium Cr(VI); nickel; manganese; iron; molybdenum; and silicon

compounds.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Exposure Guidelines There are no occupational exposure limits for stainless steels. Occupational exposure limits

apply to some components resulting from grinding, polishing, abrasive blasting, hot rolling, hot forging, thermal cutting, or welding which may produce stainless steel dust or fumes.

Chemical Name ACGIH TLV OSHA PEL NIOSH IDLH

	TIA/A 0.0 / 3	1 () TA(A) (3)	ID111 500 / 3
Manganese	TWA: 0.2 mg/m ³	(vacated) TWA: 1 mg/m ³ fume	IDLH: 500 mg/m ³
7439-96-5		(vacated) STEL: 3 mg/m ³ fume	TWA: 1 mg/m ³ fume
		(vacated) Ceiling: 5 mg/m ³	STEL: 3 mg/m ³
		Ceiling: 5 mg/m³ fume	_
Copper	TWA: 0.2 mg/m ³ fume	TWA: 0.1 mg/m ³ fume	IDLH: 100 mg/m ³ dust, fume and
7440-50-8		TWA: 1 mg/m ³ dust and mist	mist
		(vacated) TWA: 0.1 mg/m ³ Cu	TWA: 1 mg/m ³ dust and mist
		dust, fume, mist	TWA: 0.1 mg/m ³ fume
Nickel	TWA: 1.5 mg/m ³	TWA: 1 mg/m ³	IDLH: 10 mg/m ³
7440-02-0		(vacated) TWA: 1 mg/m ³	TWA: 0.015 mg/m ³
Silicon	-	TWA: 15 mg/m ³ total dust	TWA: 10 mg/m ³ total dust
7440-21-3		TWA: 5 mg/m ³ respirable	TWA: 5 mg/m ³ respirable dust
		fraction	
		(vacated) TWA: 10 mg/m ³ total	
		dust	
		(vacated) TWA: 5 mg/m ³	
		respirable fraction	
Cobalt	TWA: 0.02 mg/m ³	TWA: 0.1 mg/m ³ dust and fume	IDLH: 20 mg/m ³ dust and fume
7440-48-4	3	(vacated) TWA: 0.05 mg/m ³ dust	
		and fume	fume

Appropriate engineering controls

Engineering Measures Ensure adequate ventilation, especially in confined area (i.e. showers, eyewash stations,

etc.).

Individual protection measures, such as personal protective equipment

Eye/Face Protection
Skin and Body Protection
Respiratory Protection

When processing the metal alloy wear: Tightly fitting safety goggles. When processing the metal alloy: Wear protective gloves/clothing.

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State Solid Appearance Varying from dull very light grey,

to shiny metallic light grey to

bright mirror-finish

Odor Odorless Odor Threshold No information available

Property pH Melting Point/Range Boiling Point/Boiling Range Flash Point Evaporation rate Flammability (solid, gas) Flammability Limits in Air upper flammability limit lower flammability limit Vapor Pressure Vapor Density Relative Density Specific Gravity Water Solubility	Values No data available 1370-1520 °C / 2498-2768 °F No data available	Remarks/ - Method None known
	No data available No data available	

WPS-OUT-004 - Chromium-Nickel-Manganese-Copper Alloyed Stainless Steel

grades

Revision Date 20-Nov-2017

Viscosity No data available None known

Flammable Properties Not flammable

Explosive Properties No data available Oxidizing Properties No data available

Other information

VOC Content (%) No data available

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Dust formation.

Incompatible materials

May react in contact with strong acids to release gaseous acid decomposition products, e.g. hydrogen, oxides of nitrogen. Use of strong oxidizers (high pH) on stainless steel may cause Cr(VI) compounds to form at ambient temperatures. Decomposition: Fumes generated during welding, brazing, or thermal cutting may contain: chromium compounds, including hexavalent chromium Cr(VI); nickel; manganese; iron; molybdenum; and silicon compounds.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information In its solid form stainless steel does not present an inhalation, absorption, or ingestion

hazard. Grinding, polishing, abrasive blasting, hot rolling, hot forging,thermal cutting, or welding may produce stainless steel dust or fumes containing complex or mixed oxides (spinels) of its components. Metal dust particles may cause eye, skin and/or respiratory

system irritation. The below information is for these instances.

Inhalation May cause irritation of respiratory tract. Inhalation of fumes may cause metal fume fever,

which is characterized by flu-like symptoms with metallic taste, fever, chills, cough,

weakness, chest pain, muscle pain and increased white blood cell count. May cause allergy

or asthma symptoms or breathing difficulties if inhaled.

Eye Contact Contact with eyes may cause irritation.

Skin ContactContact with dust can cause mechanical irritation or drying of the skin. Repeated or

prolonged skin contact may cause allergic reactions with susceptible persons.

Ingestion May cause irritation

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Iron	= 984 mg/kg (Rat)	-	-
Manganese	= 9 g/kg (Rat)	-	-
Nickel	> 9000 mg/kg (Rat)	-	-
Silicon	= 3160 mg/kg (Rat)	-	-
Cobalt	= 6170 mg/kg (Rat)	-	> 10 mg/L (Rat) 1 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects and also chronic effects from short and long term exposure

Sensitization May cause sensitization by inhalation and skin contact

Mutagenic Effects No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Chromium		Group 3		
Nickel		Group 2B Group 1	Reasonably Anticipated	Х
Cobalt	A3	Group 2A Group 2B		Х

Reproductive Toxicity
STOT - single exposure
No information available.
No information available.

STOT - repeated exposureCauses damage to organs through prolonged or repeated exposure.

Chronic Toxicity Elevated temperature processing such as welding and plasma arc cutting may release

hazardous fumes. Overexposure to metal fumes may cause pulmonary edema (fluid in the lungs) and methemaglobinemia. May also cause pulmonary fibrosis and lung cancer. Chronic exposure to manganese may cause impairment to the central nervous system including sluggishness, sleepiness, muscle weakness, loss of facial muscle control, edema,

emotional disturbances, spastic gait, and falling.

Target Organ EffectsRespiratory system. Skin.Aspiration HazardNo information available.

Numerical measures of toxicity • - Product

The following values are calculated based on chapter 3.1 of the GHS document: LD50 Oral 967 mg/kg; Acute toxicity estimate 7500

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Iron	-	LC50 96 h: = 0.56 mg/L	-	-
		semi-static (Cyprinus carpio)		
		LC50 96 h: = 13.6 mg/L		
		static (Morone saxatilis)		

Copper	EC50 96 h: 0.031 - 0.054	LC50 96 h: 0.0068 - 0.0156	_	EC50 48 h: = 0.03 mg/L
Соррег	mg/L static	mg/L (Pimephales		Static (Daphnia magna)
	(Pseudokirchneriella	promelas)		Statio (Bapillia magna)
	subcapitata)	LC50 96 h: < 0.3 mg/L static		
	EC50 72 h: 0.0426 - 0.0535			
		(
	mg/L static	LC50 96 h: = 0.052 mg/L		
	(Pseudokirchneriella	flow-through (Oncorhynchus		
	subcapitata)	mykiss)		
		LC50 96 h: = 0.112 mg/L		
		flow-through (Poecilia		
		reticulata)		
		LC50 96 h: = 0.2 mg/L flow-		
		through (Pimephales		
		promelas)		
		LC50 96 h: = 0.3 mg/L semi-		
		static (Cyprinus carpio)		
		LC50 96 h: = 0.8 mg/L static		
		(Cyprinus carpio)		
		LC50 96 h: = 1.25 mg/L		
		static (Lepomis macrochirus)		
Nickel	EC50 96 h: 0.174 - 0.311	LC50 96 h: = 1.3 mg/L semi-	-	EC50 48 h: = 1 mg/L Static
	mg/L static	static (Cyprinus carpio)		(Daphnia magna)
	(Pseudokirchneriella	LC50 96 h: = 10.4 mg/L		EC50 48 h: > 100 mg/L
	` subcapitata)	static (Cyprinus carpio)		(Daphnia magna)
	EC50 72 h: = 0.18 mg/L	LC50 96 h: > 100 mg/L		` ' ' ' '
	(Pseudokirchneriella	(Brachydanio rerio)		
	subcapitata)	, ,		
Cobalt	-	LC50 96 h: > 100 mg/L static	-	-
		(Brachydanio rerio)		

Persistence and Degradability

No information available.

Bioaccumulation

No information available.

Other Adverse Effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Recover or recycle if possible. Dispose of in accordance with federal, state, and local

regulations

Contaminated Packaging Dispose of in accordance with federal, state, and local regulations.

Chemical Name	RCRA	RCRA - Basi	s for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Chromium - 7440-47-3		Included in w	aste streams:	5.0 mg/L regulatory level	
		F032, F034,	F035, F037,		
		F038,	F039		
Nickel - 7440-02-0	(hazardous constituent - no	Included in w	aste streams:		
	waste number)	F006,	F039		
	Chemical Name			California Hazardous	s Waste
	Chromium		Toxic		
				Corrosive	
				Ignitable	
	Manganese			Ignitable powde	er
	Copper		Toxic		
	Nickel		Toxic powder		
		Ignitable powder			
Cobalt		Toxic powder			
			Ignitable powde	er	
Titanium		Ignitable powder			

14. TRANSPORT INFORMATION

DOT Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies Complies

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Chromium	7440-47-3	15.5-17.5	1.0
Manganese	7439-96-5	6.5-9	1.0
Copper	7440-50-8	2-4	1.0
Nickel	7440-02-0	1.5-3.5	0.1
Cobalt	7440-48-4	0-0.6	0.1

SARA 311/312 Hazard Categories

Acute Health HazardNoChronic Health HazardNoFire HazardNoSudden Release of Pressure HazardNoReactive HazardNo

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Copper		X	X	
Nickel		X	Х	

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Chromium			RQ 5000 lb final RQ
			RQ 2270 kg final RQ
Copper	5000 lb		RQ 5000 lb final RQ
			RQ 2270 kg final RQ
Nickel	100 lb		RQ 100 lb final RQ
			RQ 45.4 kg final RQ

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Nickel	7440-02-0	Carcinogen
Cobalt	7440-48-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Chromium		X			X
Manganese	Х	X	Х	Х	Х
Copper	X	X	X	X	X
Nickel	X	X	X	X	X
Silicon	X	X	X		X
Cobalt	Х	X	Х	Х	Х
Titanium	X				

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION								
NFPA	Health Hazard 0	Flammability	0	Instability 0	Physical and Chemical Hazards -			
<u>HMIS</u>	Health Hazard 0	Flammability	0	Physical Hazard 0	Personal Protection X			

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110 1-800-572-6501

Issuing Date26-Nov-2012Revision Date26-Nov-2012Revision NoteInitial Release.

General Disclaimer

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet